



CHANGHUA DIAMOND INDUSTRIAL CO., LTD

Address: No. 100, Lane 395, Minyi St. Sioushlei Township,
Changhua County 504, Taiwan

TEL: 886-4-7688722 Whatsapp: 886 923 296 638

Web: chd-amigo.com



E-mail: chd.diamond@msa.hinet.net, chd.diamond@gmail.com



WeChat

PORTABLE TILE CUTTER (Cutter can be changed between 45°/90°)

Feature: Three pieces design can be used conveniently




60A1 / 100A1 / 120A1

MODEL	BLADE	CAPABILITY	VOLTAGE	RPM	KG
60A1	4"	60CM*2CM	110V/220V	11000	28
100A1	4"	100CM*2CM	110V/220V	11000	35
120A1	4"	120CM*2CM	110V/220V	11000	42

45° TILE CUTTER (Cutter can be changed between 45°/90°)

Feature: Three pieces design can be used conveniently



45A60 / 45A100 / 45A120

MODEL	BLADE	CAPABILITY	VOLTAGE	RPM	KG
45A60	4"	60CM*2CM	110V/220V	11000	28
45A100	4"	100CM*2CM	110V/220V	11000	35
45A120	4"	120CM*2CM	110V/220V	11000	42

STRONG TILE CUTTING MACHINE

Feature:Multi-Function with cutting straight , anti-slid groove & grounding edge




S180 / M180

MODEL	BLADE	CAPABILITY	VOLTAGE	RPM	KG
S180	4"-7"	60CM*5CM	110V/220V	6500	38
M180	4"-7"	100CM*5CM	110V/220V	6500	58

STRONG AUTO TILE CUTTING MACHINE

Feature:Change between manual or auto cutting easily



S180LA / M180LA / L180LA

MODEL	BLADE	CAPABILITY	VOLTAGE	RPM	KG
S180A	4"-7"	60CM*5CM	110V/220V	6500	40
M180A	4"-7"	100CM*5CM	110V/220V	6500	60
L180A	4"-7"	120CM*5CM	110V/220V	6500	70

AUTOMATIC HOMOGENEOUS TILE CUTTING MACHINE

Feature: Design for homogeneous tile, can change between auto and manual



S110 / M110 / L110

MODEL	BLADE	CAPABILITY	VOLTAGE	RPM	KG
S110	4"	60cm*2.5cm	110V/220V	11000	44
M110	4"	100cm*2.5cm	110V/220V	11000	54
L110	4"	120cm*2.5cm	110V/220V	11000	64

RAIL TYPE CUTTING SAW

Feature: For large stone slab, can extend length



H3

MODEL	BLADE	CAPABILITY	VOLTAGE	RPM	KG
H3	10"	300cm*4cm	110V/220V	6500	40

10" HEAVY DUTY CUTTING MACHINE

Feature: 3HP power for cutting thick stone



S250 / M250 / L250

MODEL	BLADE	CAPABILITY	VOLTAGE	RPM	KG
S250	10"	60cm*7cm	220V	2000	70
M250	10"	90cm*7cm	220V	2000	80
L250	10"	120cm*7cm	220V	2000	90

14" HEAVY DUTY CUTTING MACHINE

Feature: Cutting very thick stone




M350

MODEL	BLADE	CAPABILITY	VOLTAGE	RPM	KG
M350	14"	60cm*12cm	220V	2000	90

HEAVY-DUTY ANGLE CUTTING MACHINE

Feature: Specially for angle cutting




SA250


MODEL	BLADE	CAPABILITY	VOLTAGE	RPM	KG
SA250	10"	60cm*7cm	220V	2000	70

SIDE CUTTING MACHINE

Feature: Cutting tile side, can adjust depth and up/down




BE-1



MODEL	BLADE	CAPABILITY	VOLTAGE	RPM	KG
BE-1	4"	2CM	110V/220V	10000	9

BOTTOM BEVEL CUTTING MACHINE

Feature: Design for 45 degree bevel cutting, light and portable for any length



D45N

Manufacturing drawing

MODEL	BLADE	CAPABILITY	VOLTAGE	RPM	KG
D45N	7"	10MM-40MM	110V/220V	6000	10

CIRCULAR CUTTING MACHINE

Feature: Portable & east to cut round table



CX-200

Radius: 20cm-100cm

MODEL	BLADE	CAPABILITY	VOLTAGE	RPM	KG
CX-200	4"	10MM-40MM	110V/220V	1100	10

VACUUM SUCTION BACK BOLT REAMING MACHINE

Feature:


Dry type installation of exterior wall

Vacuum suction design can be set on non-flat surface without making any damage

Center injection cooling system & Solid drill bit



CO-2



Manufacturing drawing



MODEL	HOLE	DEPTH	VOLTAGE	RPM	SUCTION PRESSURE	WEIGHT
CO-2	8-12MM	16MM	110V/220V	4500	100KG	14.2KG

VACUUM SUCTION SIDE-DRILLING MACHINE

Feature:


Dry type installation of exterior wall

Vacuum suction design can be set on non-flat surface without making any damage

High mobility with portable water bucket



CO-3



MODEL	HOLE	VOLTAGE	RPM	SUCTION PRESSURE	WEIGHT
CO-3	8-12MM	110V/220V	12000	100KG	11KG

CENTER INJECTION HIGH SPEED SINGLE SUCTION DRILLER

Feature: Specifically for plastic bolts of 6/8/10/12 mm
The best choice to install implements such as bathroom & window works
Work in brand new concept with portable water tank pump
High speed drilling without damage stone



W-38



MODEL	HOLE	DEPTH	VOLTAGE	RPM	SUCTION PRESSURE	WEIGHT
W-38	6-12MM	30MM	110V/220V	15000	50KG	3.8KG

DOUBLE SUCTION STONE DRILLER

Feature: Fix precisely, easy to operate



3200



3300




3400
(Vacuum Suction)


MODEL	CORE BIT	CAPABILITY	VOLTAGE	POWER	RPM	KG
3200	6-90MM	90MM	110V/220V	1400W	750	10
3300	6-160MM	160MM	110V/220V	1600W	750	11
3400	6-70MM	70MM	110V/220V	1600W	750	12

LIGHT GROUNDING EDGE MACHINE (Hydrofloat or Ball bottom)

Feature: Variety choice & Light weight



MX1250A



MX1260


MODEL	DIAMOND WHEEL	CAPABILITY	VOLTAGE	RPM	KG
MX1250A	80MM	1CM~2CM	110V/220V	11000	8
MX1260	80MM	1CM~2CM	110V/220V	9000	10

STRONG GROUNDING EDGE MACHINE (Ball bottom)

Feature: Variety choice , Cutting straight , curve or interior & exterior circle



MX1280



MX1280N



MX1290
(Top Bevel)

MODEL	DIAMOND WHEEL	CAPABILITY	VOLTAGE	RPM	KG
MX1280	90MM	1CM~4CM	110V/220V	8500	17
MX1280N	90MM	1CM~4CM	110V/220V	0~8500	18
MX1290	90MM	1CM~4CM	110V/220V	8500	20

LIGHT-DUTY CUTTING EDGE MACHINE (Hydrofloat or Ball bottom)

Feature: Safety with insulation & Hydrofloat bottom without scraping surface



M1



M2



CP-1



M2N

MODEL	DIAMOND WHEEL	CAPABILITY	VOLTAGE	RPM	KG
M1	90MM	1CM~4CM	110V/220V	8500	15
M2	90MM	1CM~4CM	110V/220V	8500	15
M2N	90MM	1CM~4CM	110V/220V	0-8500	16
CP-1	90MM	1CM~4CM	110V/220V	5000	38

HEAVY-DUTY CUTTING EDGE MACHINE (Hydrofloat or Ball bottom)

Feature: Strong power, Safety with insulation, Hydrofloat bottom without scraping surface



M3



M4



M4S



M5

MODEL	DIAMOND WHEEL	CAPABILITY	VOLTAGE	RPM	KG
M3	90MM	1CM~4CM	THREE PHASE / 220V	8500	35
M4	90MM	1CM~4CM	THREE PHASE /220V	8500	25
M4S	90MM	1CM~4CM	SINGLE PHASE /220V	3000~10000	25
M5	90MM	1CM~4CM	SINGLE PHASE /220V	3000~10000	36

LIGHT-DUTY SIX STEP ROUTER

Feature: Doing great from grinding to polishing
Without changing polishing wheel



S6

MODEL	DIAMOND WHEEL	CAPABILITY	VOLTAGE	RPM	KG
S6	75MM	1CM~2CM	110V/220V	11000	22

HEAVY-DUTY SIX STEP ROUTER

Feature: 3HP power does great from grinding to polishing
Without changing polishing wheel




M6


MODEL	DIAMOND WHEEL	CAPABILITY	VOLTAGE	RPM	KG
M6	90MM	1CM~4CM	SINGLE PHASE /220V	11000	49

CURVE CUTTING MACHINE

Feature: Work great for cutting any groove of sink



Q1




MODEL	DIAMOND TOOL	PROCESS THE SCOPE	VOLTAGE	RPM	KG
Q1	16MM	ARBITRARY	110V/220V	18000	15

PNEUMATIC ANGLE POLISHING MACHINE(Table-Rail Style)

Feature:Work great for any angle, polishing crystal shine
Change backing pads quickly & easily with magnet backing pads
The length of worktable can be customized




R-2



MODEL	POLISHING PAD	AIR PRESS	RPM	LENGTH
R-2	80MM	6-7KG	4500	120CM/150CM/CUSTOMIZED

PNEUMATIC ANGLE POLISHING MACHINE(Suction-Rail Style)

Feature:Length of rail can be customized
Work great for any angle, polishing crystal shine
Change backing pads quickly & easily with magnet backing pads



R-1




Magnet Pads

MODEL	POLISHING PAD	AIR PRESS	RPM	LENGTH
R-1	80MM	6-7KG	4500	110CM/160CM/CUSTOMIZED

PNEUMATIC WATER SANDER

Feature: Best-selling, long life time




S9

MODEL	POLISHING PAD	AIR PRESSURE	AIR CONS	RPM	KG
S9 Orange	3" or 4"	6~7kg(90psi)	0.45m ³ /min	0~4500	1.2
S9 Black	3" or 4"	6~7kg(90psi)	0.45m ³ /min	0~4500	1.2
S9 Green	3" or 4"	6~7kg(90psi)	0.45m ³ /min	0~4500	1.2

REAR EXHAUST PNEUMATIC WATER SANDER

Feature: Small sound & cold proofing with rear exhaust function
Light weight & High speed rotation



SA2

MODEL	POLISHING PAD	AIR PRESSURE	AIR CONS	RPM	KG
SA2	4"	6~7kg(90psi)	0.45m ³ /min	0~4000	1.4

ELECTRICAL WATER SANDER

Feature:Light weight & Portable



PF3206




PF3210A

MODEL	POLISHING PAD	CAPABILITY	VOLTAGE	RPM	KG
PF3206	3"	3"	110V/220V	4500	2
PF3210A	4"	3"-4"	110V/220V	4500	4

ELECTRICAL SANDER

Feature:Wide surface polishing



B10



MODEL	BACKING SIZE	CAPABILITY	VOLTAGE	RPM	KG
B10	10"	3"-4"	110V/220V	8500	7.6

ELECTRIC ANGLE POLISHING MACHINE

Feature: Portable, operate easily and & widely without length limit. Change backing pads quickly & easily with magnet design



MODEL	POLISHING PAD	VOLTAGE	RPM	KG
R-3	3"-4"	110V/220V	4500	12

PNEUMATIC ANGLE POLISHING MACHINE

Feature: Portable, operate easily and & widely without length limit. Change backing pads quickly & easily with magnet design



MODEL	POLISHING PAD	PRESSURE	RPM	KG
R3A	3"-4"	6-7KG	11000	9.5

HYDRO-FLOAT INTERNAL CURVE POLISHER

Feature: Work great for internal and external curve, polishing crystal shine
Hydro-float make no damage on stone surface
Do polish on any stone with 0-8500 rpm



Q-3



MODEL	CAPABILITY	VOLTAGE	RPM	KG
Q3	1-4CM	110V/220V	8500	7.6


OTHER PRODUCTS



GM8 Dry polisher



CHD-7 Pneumatic chisel



Manual tile cutter



4" Stone saw




4" Angle grinder



Mix machine



Single & double suction cap



Diamond core bit-feed water adapter




Any type of adapter


DIAMOND BLADES & DIAMOND TOOLS




Diamond polisher pad



4" Stone blade




4" Tile blade




Electroplated blade



4" Diamond cup




5" Diamond blade




7" Stone blade



7" Tile blade




8" Diamond blade




10" Stone blade



10" Tile blade



12"~16" Stone blade



12"~24" Road blade



30" Wall blade



Diamond core bit



Diamond core bit-
feed water



Diamond finger bits



Diamond profile bits



Diamond core bit-
electroplated



Diamond core bit-
brazed




Diamond wheel &
polishing wheel




Diamond wheel-
brazed



Diamond wheel-
electroplated



12"Grooving wheel-
Brazed



12"Grooving wheel-
electroplated

MAGNET BACKING PADS



Feature: Change polishing pads much faster & convenient with magnet design

